



Safety Data Sheet

Material Name: ArmaKleen Paint and Ink Remover: Mixture

SDS ID: 82978

Section 1 - PRODUCT AND COMPANY IDENTIFICATION

Material Name

ArmaKleen Paint and Ink Remover: Mixture

Product Code

Not applicable.

Synonyms

Not available.

Product Use Recommended Use

Organic paint and ink and paint coating removal system. Product is designed to remove paints and inks from aluminum and steel. If this product is used in combination with other products, refer to the Safety Data Sheet for those products.

Restrictions on Use

For professional use only.

MANUFACTURER

Church & Dwight
The ArmaKleen™ Company
469 North Harrison Street
Princeton, NJ 08543
Phone: (800) 332-5424
www.churchdwight.com

SUPPLIER (in the U.S.A.)

Safety-Kleen Systems, Inc.
42 Longwater Drive
Norwell, MA 02061-9149
Phone: 1-800-669-5740
www.safety-kleen.com

SUPPLIER (in Canada)

Safety-Kleen Canada Inc.
25 Regan Road
Brampton, Ontario, Canada L7A 1B2
Phone: 1-800-669-5740

Emergency Telephone Number

Medical: 1-888-234-1828 Chemical: 1-800-424-9300 (CHEMTREC)

Issue Date

September 23, 2020

Supersedes Issue Date

March 6, 2017

Original Issue Date

September 1, 2004

Section 2 - HAZARDS IDENTIFICATION

Classification in accordance with Schedule 1 of Hazardous Products Regulations (HPR) (SOR/2015-17)

Acute Toxicity - Inhalation - Dust/Mist - Category 4

Serious Eye Damage/Eye Irritation - Category 2A

Skin Sensitization - Category 1A

GHS Label Elements

Symbol(s)



Signal Word

Safety Data Sheet

Material Name: ArmaKleen Paint and Ink Remover: Mixture

SDS ID: 82978

Danger.

Hazard Statement(s)

Harmful if inhaled.
Causes serious eye irritation.
May cause allergic skin reaction.

Precautionary Statement(s)

Prevention

Avoid breathing vapor or mist. Use only outdoors or in a well-ventilated area. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Contaminated work clothing should not be allowed out of the workplace.

Response

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

Storage

Store locked up. Do not store below 40°F (4.4 °C)

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards

Contact with heated material may cause serious thermal burns.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component Name	Percent
7732-18-5	Water	38-42
100-51-6	Benzyl alcohol	36-39
124-68-5	2-Amino-2-methyl-1-propanol	5.9 – 6.6
68439-46-3	Alcohols, C9-11, ethoxylated	1.2 – 1.3
34398-01-1	Poly(oxy-1,2-ethanediyl), .alpha.-undecyl-.omega.-hydroxy-	1.2 – 1.3
1300-72-7	Sodium xylene sulfonate	0.5-1.5
23783-26-8	Acetic acid, hydroxyphosphono-	0.12-0.13

Section 4 - FIRST AID MEASURES

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician.

Skin

IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. For thermal burns caused by

Safety Data Sheet

Material Name: ArmaKleen Paint and Ink Remover: Mixture

SDS ID: 82978

contact with hot product, remove affected clothing and shoes. Wash skin thoroughly with cool water. Apply cool-packs or ice.

Eyes

IF IN EYES: Immediately flush eyes with a directed stream of water for at least 15 minutes, forcibly holding eyelids apart to ensure complete irrigation of all eye and lid tissue. Remove contact lenses, if present, after the first five minutes and continue rinsing the eye. Immediately call a POISON CENTER or doctor/physician.

Ingestion

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

Most Important Symptoms/Effects

Acute

Harmful if inhaled. Causes serious eye irritation. May cause allergic skin reaction.

Delayed

Repeated exposure may cause skin dryness or cracking.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically and supportively. HOT LIQUID CAN CAUSE SEVERE BURNS TO THE EYES AND SKIN which can result in permanent eye damage.

Section 5 - FIRE FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Use extinguishing agents appropriate for surrounding fire.

Unsuitable Extinguishing Media

Do not use high-pressure water streams.

Special Hazards Arising from the Chemical

Negligible fire hazard.

Hazardous Combustion Products

Decomposition and combustion materials may be toxic. Burning may produce Carbon monoxide.

Fire Fighting Measures

Move container from fire area if it can be done without risk. Keep storage containers cool with water spray. "Empty" containers may retain residue and can be dangerous. Product is not sensitive to mechanical impact or static discharge.

Special Protective Equipment and Precautions for Firefighters

A positive-pressure, self-contained breathing apparatus (SCBA) and full-body protective equipment are required for fire emergencies.

Section 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Wear personal protective clothing and equipment, see Section 8.

Methods and Materials for Containment and Cleaning Up

Remove all ignition sources. Do not touch or walk through spilled product. Keep unnecessary and unprotected personnel from entering. Ventilate area and avoid breathing vapor or mist. Contain spill as a liquid for possible recovery, or sorb with compatible sorbent material and shovel with a clean, spark proof tool into a sealable container for disposal. Additionally, for large spills: Dike far ahead of liquid spill for collection and later disposal.

Environmental Precautions

Prevent material from entering drains or sewers.

Safety Data Sheet

Material Name: ArmaKleen Paint and Ink Remover: Mixture

SDS ID: 82978

Section 7 - HANDLING AND STORAGE

Precautions for Safe Handling

Do not store below 40°F (4.4°C) Keep away from sparks or flame. Avoid breathing vapor or mist. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling.

Conditions for Safe Storage, Including any Incompatibilities

Store locked up.

Keep container tightly closed when not in use and during transport. Store containers in a cool, dry place. Do not pressurize, cut, weld, braze, solder, drill, or grind containers. Keep containers away from heat, flame, sparks, static electricity, or other sources of ignition. Empty product containers may retain product residue and can be dangerous.

Incompatible Materials

Strong acids, reducing agents, oxidizers.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Component Exposure Limits

Canada and ACGIH have not developed exposure limits for any of this product's components.

ACGIH - Threshold Limit Values - Biological Exposure Indices (BEI)

There are no biological limit values for any of this product's components.

Engineering Controls

Provide general ventilation. Where adequate general ventilation is unavailable, use process enclosures, local exhaust ventilation, or other engineering controls.

Individual Protection Measures, such as Personal Protective Equipment

Eye/face protection

Wear safety glasses. Additional protection like goggles, face shields, or respirators may be needed dependent upon anticipated use and concentrations of mists or vapors. Eye wash fountain and emergency showers are recommended. Contact lens use is not recommended.

Respiratory Protection

A respiratory protection program which meets USA's OSHA General Industry Standard 29 CFR 1910.134 or Canada's CSA Standard Z94.4-M1982 requirements must be followed whenever workplace conditions warrant a respirator's use. Consult a qualified Industrial Hygienist or Safety Professional for respirator selection guidance

Skin Protection/Glove Recommendations

Where skin contact is likely, wear gloves impervious to product; use of natural rubber (latex) or equivalent gloves is not recommended. To avoid prolonged or repeated contact where spills and splashes are likely, wear appropriate chemical-resistant face shield, boots, apron, whole body suits or other protective clothing. When product is heated and skin contact is likely, wear heat-resistant gloves, boots, and other protective clothing.

Protective Materials

Personal protective equipment should be selected based upon the conditions under which this material is used. A hazard assessment of the work area for PPE requirements should be conducted by a qualified professional pursuant to regulatory requirements. The following PPE should be considered the minimum required: Safety glasses, Gloves, Lab coat or apron.

Safety Data Sheet

Material Name: ArmaKleen Paint and Ink Remover: Mixture

SDS ID: 82978

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Clear, Pale yellow liquid	Physical State	Liquid
Odor	Aromatic	Color	Pale yellow
Odor Threshold	Not available	pH	10 - 11
Melting Point	<0 °C (32°F)	Boiling Point	>121 °C (250°F)
Boiling Point Range	Not available	Freezing point	Not available
Evaporation Rate	Equal to Water.	Flammability (solid, gas)	Not available
Autoignition Temperature	321 °C (609°F)	Flash Point	109 °C (228°F)
Lower Explosive Limit	Not available	Decomposition temperature	Not available
Upper Explosive Limit	Not available	Vapor Pressure	15 mm Hg @ 20 °C
Vapor Density (air=1)	Not available	Specific Gravity (water=1)	1.009
Water Solubility	Not available	Partition coefficient: n-octanol/water	Not available
Viscosity	Not available	Kinematic viscosity	Not available
Solubility (Other)	Not available	Density	8.4 lb/US gal (1009 g/L)
Molecular Weight	Not available		
Volatile Organic Compounds (As regulated)	47.2 WT%; 3.96 LB/US gal; 475 g/L; As per 40 CFR Part 51.100(s) Product Vapor Pressure @20°C = 15.0 mmHg Product may or may not be considered photochemically reactive. Consult your state or local air district regulations for location specific information. VOC Vapor Pressure <0.1 mm Hg @ 68°F (20°C)		

Section 10 - STABILITY AND REACTIVITY

Reactivity

May react on contact with Strong acid.

Chemical Stability

Stable under normal temperatures and pressures.

Possibility of Hazardous Reactions

Polymerization is not known to occur under normal temperature and pressures. Not reactive with water.

Conditions to Avoid

Avoid sparks or flame, direct sunlight, moisture.

Incompatible Materials

Avoid oxidizing agents, reducing agents, strong acids.

Hazardous decomposition products

None under normal temperatures and pressures. See also SECTION 5: HAZARDOUS COMBUSTION PRODUCTS.

Safety Data Sheet

Material Name: ArmaKleen Paint and Ink Remover: Mixture

SDS ID: 82978

Thermal decomposition products

Carbon monoxide.

Section 11 - TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Inhalation

Harmful if inhaled. May cause narcotic effects in high concentrations. Symptoms may include headache, dizziness, nausea, loss of coordination.

Skin Contact

May cause skin irritation. May cause an allergic skin reaction. Contact with heated material may cause serious thermal burns.

Eye Contact

Causes serious eye irritation. May cause blurred vision and tearing.

Ingestion

May be harmful if swallowed. May cause irritation.

Acute and Chronic Toxicity

Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

Benzyl alcohol (100-51-6)

Oral LD50 Rat 1230 mg/kg Dermal LD50 Rabbit 2 g/kg Inhalation LC50 Rat 8.8 mg/L 4 h

2-Amino-2-methyl-1-propanol (124-68-5)

Oral LD50 Rat 2900 mg/kg (in physiological saline) Dermal LD50 Rabbit >2000 mg/kg (no deaths occurred)

Alcohols, C9-11, ethoxylated (68439-46-3)

Oral LD50 Rat 1400 mg/kg

Sodium xylene sulfonate (1300-72-7)

Oral LD50 Rat 1000 mg/kg

Product Toxicity Data

Product Analysis LD/LC 50 Toxicity Values

Inhalation LC50:	4 mg/l 4 hr
------------------	-------------

Acute Toxicity Estimate

No data available.

Immediate Effects

Harmful if inhaled. Causes serious eye irritation. May cause allergic skin reaction.

Delayed Effects

Repeated exposure may cause skin dryness or cracking.

Irritation/Corrosivity Data

Causes serious eye irritation. May cause respiratory tract irritation and skin irritation.

Respiratory Sensitization

Based on best current information, there is no known human sensitization associated with this product.

Dermal Sensitization

No information on significant adverse effects. May cause allergic skin reaction.

Component Carcinogenicity

None of this product's components are listed by ACGIH, IARC, NTP, DFG or OSHA.

Germ Cell Mutagenicity

Based on best current information, there is no known teratogenicity associated with this product.

Experimental evidence suggests that this product does not cause mutagenesis.

Safety Data Sheet

Material Name: ArmaKleen Paint and Ink Remover: Mixture

SDS ID: 82978

Tumorigenic Data

No data available

Reproductive Toxicity

Based on best current information, there is no known reproductive toxicity associated with this product.

Specific Target Organ Toxicity - Single Exposure

No target organs identified.

Specific Target Organ Toxicity - Repeated Exposure

No target organs identified.

Aspiration hazard

Based on available data, the classification criteria are not met.

Medical Conditions Aggravated by Exposure

Individuals with pre-existing respiratory tract (nose, throat, and lungs), eye, and/or skin disorders may have increased susceptibility to the effects of exposure.

Section 12 - ECOLOGICAL INFORMATION

Component Analysis - Aquatic Toxicity

Benzyl alcohol	100-51-6
Fish:	LC50 96 h Pimephales promelas 460 mg/L [static]; LC50 96 h Lepomis macrochirus 10 mg/L [static]
Invertebrate:	EC50 48 h water flea 23 mg/L
2-Amino-2-methyl-1-propanol	124-68-5
Fish:	LC50 96 h Lepomis macrochirus 190 mg/L [static]
Algae:	EC50 72 h Desmodesmus subspicatus 520 mg/L IUCLID
Invertebrate:	EC50 48 h Daphnia magna 193 mg/L IUCLID

Invertebrate Toxicity

No additional information is available.

Persistence and Degradability

No information available for the product.

Bioaccumulative Potential

No information available for the product.

Mobility

No information available for the product.

Section 13 - DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose in accordance with federal, state, provincial, and local regulations. Regulations may also apply to empty containers. The responsibility for proper waste disposal lies with the owner of the waste. Contact ArmaKleen regarding proper recycling or disposal.

Safety Data Sheet

Material Name: ArmaKleen Paint and Ink Remover: Mixture

SDS ID: 82978

Section 14 - TRANSPORT INFORMATION

US DOT Information: Not regulated for transport.

TDG Information: Not regulated for transport.

IATA Information: Not regulated for transport.

Further information: Not regulated for transport.

IMDG Information: Not regulated for transport.

Further information: Not regulated as dangerous goods.

International Bulk Chemical Code

This material contains one or more of the following chemicals required by the IBC Code to be identified as dangerous chemicals in bulk.

Benzyl alcohol	100-51-6
IBC Code:	Category Y
2-Amino-2-methyl-1-propanol	124-68-5
IBC Code:	Category Z
Alcohols, C9-11, ethoxylated	68439-46-3
IBC Code:	Category Y

Section 15 - REGULATORY INFORMATION
--

Canada Regulations

CEPA - Priority Substances List

None of this product's components are on the list.

Ozone Depleting Substances

None of this product's components are on the list.

Council of Ministers of the Environment - Soil Quality Guidelines

None of this product's components are on the list.

Council of Ministers of the Environment - Water Quality Guidelines

None of this product's components are on the list.

U.S. Federal Regulations

None of this product's components are listed under SARA Sections 302/304 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), or require an OSHA process safety plan.

SARA Section 311/312 (40 CFR 370 Subparts B and C) reporting categories:

Acute toxicity; Skin Corrosion/Irritation; Respiratory/Skin Sensitization; Serious Eye Damage/Eye Irritation; Specific Target Organ Toxicity

California

Not listed under California Proposition 65.

Component Analysis - Inventory

Benzyl alcohol (100-51-6)

US	CA	AU	CN	EU	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2
Yes	DSL	Yes	Yes	EIN	Yes	Yes	Yes	No

Safety Data Sheet

Material Name: ArmaKleen Paint and Ink Remover: Mixture

SDS ID: 82978

KR - REACH CCA	MX	NZ	PH	TH-TECI	TW	VN (Draft)
No	Yes	Yes	Yes	Yes	Yes	Yes

2-Amino-2-methyl-1-propanol (124-68-5)

US	CA	AU	CN	EU	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2
Yes	DSL	Yes	Yes	EIN	Yes	Yes	Yes	No
KR - REACH CCA		MX	NZ	PH	TH-TECI	TW	VN (Draft)	
No		Yes	Yes	Yes	Yes	Yes	Yes	

Alcohols, C9-11, ethoxylated (68439-46-3)

US	CA	AU	CN	EU	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2
Yes	DSL	Yes	Yes	No	No	No	Yes	No

KR - REACH CCA	MX	NZ	PH	TH-TECI	TW	VN (Draft)
No	Yes	Yes	Yes	Yes	Yes	Yes

Poly(oxy-1,2-ethanediyl), .alpha.-undecyl-.omega.-hydroxy- (34398-01-1)

US	CA	AU	CN	EU	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2
Yes	DSL	Yes	Yes	No	No	No	Yes	No
KR - REACH CCA		MX	NZ	PH	TH-TECI	TW	VN (Draft)	
No		No	Yes	Yes	No	Yes	Yes	

Sodium xylene sulfonate (1300-72-7)

US	CA	AU	CN	EU	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2
Yes	DSL	Yes	Yes	EIN	Yes	Yes	Yes	No
KR - REACH CCA		MX	NZ	PH	TH-TECI	TW	VN (Draft)	
No		Yes	Yes	Yes	Yes	Yes	Yes	

Safety Data Sheet

Material Name: ArmaKleen Paint and Ink Remover: Mixture

SDS ID: 82978

Acetic acid, hydroxyphosphono- (23783-26-8)

US	CA	AU	CN	EU	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2
Yes	DSL	Yes	Yes	EIN	No	Yes	Yes	No
KR - REACH CCA			MX	NZ	PH	TH-TECI	TW	VN (Draft)
No			No	Yes	Yes	Yes	Yes	Yes

Section 16 - OTHER INFORMATION

NFPA Ratings

Health: 2 Fire: 0 Instability: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Summary of Changes

Regulatory review and update.

Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CA/MA/MN/NJ/PA - California/Massachusetts/Minnesota/New Jersey/Pennsylvania*; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CFR - Code of Federal Regulations (US); CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD - Dangerous Substance Directive; DSL - Domestic Substances List; EC - European Commission; EEC - European Economic Community; EIN - European Inventory of (Existing Commercial Chemical Substances); EINECS - European Inventory of Existing Commercial Chemical Substances; ENCS - Japan Existing and New Chemical Substance Inventory; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; F - Background (for Venezuela Biological Exposure Indices); IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; ISHL - Japan Industrial Safety and Health Law; IUCLID - International Uniform Chemical Information Database; JP - Japan; Kow - Octanol/water partition coefficient; KR KECI Annex 1 - Korea Existing Chemicals Inventory (KECI) / Korea Existing Chemicals List (KECL); KR KECI Annex 2 - Korea Existing Chemicals Inventory (KECI) / Korea Existing Chemicals List (KECL), KR - Korea; LD50/LC50 - Lethal Dose/ Lethal Concentration; KR REACH CCA - Korea Registration and Evaluation of Chemical Substances Chemical Control Act; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of Lists™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; MX - Mexico; Ne - Non-specific; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; Nq - Non-quantitative; NSL - Non-Domestic Substance List (Canada); NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PEL - Permissible Exposure Limit; PH - Philippines; RCRA - Resource Conservation and Recovery Act; REACH - Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; Sc - Semi-quantitative; STEL - Short-term Exposure Limit; TCCA - Korea Toxic Chemicals Control Act; TDG - Transportation of Dangerous Goods; TH-TECI - Thailand - FDA Existing Chemicals Inventory (TECI); TLV - Threshold Limit Value; TSCA - Toxic Substances Control Act; TW - Taiwan; TWA - Time Weighted Average; UEL - Upper Explosive Limit; UN/NA - United Nations /North American; US - United

Safety Data Sheet

Material Name: ArmaKleen Paint and Ink Remover: Mixture

SDS ID: 82978

States; VLE - Exposure Limit Value (Mexico); VN (Draft) - Vietnam (Draft); WHMIS - Workplace Hazardous Materials Information System (Canada).

Other Information

Disclaimer:

User assumes all risks incident to the use of this product. To the best of our knowledge, the information contained herein is accurate. However, ArmaKleen assumes no liability whatsoever for the accuracy or completeness of the information contained herein. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to the information or the product to which the information refers. The data contained on this sheet apply to the product as supplier to the user.