



Performance Plus Ultra Calcium Sulfonate 1, 5% Moly

Safety Data Sheet

SDS ID: 820373

Section 1 - PRODUCT AND COMPANY IDENTIFICATION

Material Name

Performance Plus Ultra Calcium Sulfonate 1, 5% Moly

Product Code

Prefix 29

Synonyms

Petroleum based grease

Product Use Recommended Use

Lubricating grease. If this product is used in combination with other products, refer to the Safety Data Sheet for those products.

Restrictions on Use

None known.

FOR PRODUCT MANUFACTURED IN THE U.S.A.:

MANUFACTURER

Safety-Kleen Systems, Inc.
42 Longwater Drive
Norwell, MA 02061-9149
U.S.A.

SUPPLIER (in Canada)

Safety-Kleen Canada, Inc.
25 Regan Road
Brampton, Ontario, L7A 1B2
Canada

FOR PRODUCT MANUFACTURED IN CANADA:

MANUFACTURER

Safety-Kleen Canada Inc.
25 Regan Road
Brampton, Ontario, L7A 1B2
Canada

SUPPLIER (in the U.S.A.)

Safety-Kleen Systems, Inc.
42 Longwater Drive
Norwell, MA 02061-9149
U.S.A.

www.safety-kleen.com

Phone: 1-800-669-5740

Emergency Phone #: 1-800-468-1760

Issue Date

July 30, 2018

Supersedes Issue Date

June 1, 2017

Original Issue Date

June 1, 2017

Section 2 - HAZARDS IDENTIFICATION

Classification in accordance with Schedule 1 of Canada's Hazardous Products Regulations (HPR) (SOR/2015-17) and paragraph (d) of 29 CFR 1910.1200 in the United States

Skin Corrosion/Irritation - Category 2

Serious Eye Damage/Eye Irritation - Category 2A

Safety Data Sheet
Performance Plus Ultra Calcium Sulfonate 1, 5% Moly

SDS ID: 820373

GHS Label Elements

Symbol(s)



Signal Word

Warning

Hazard Statement(s)

Causes skin irritation and serious eye irritation.

Precautionary Statement(s)

Prevention

Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling.

Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

Storage

None needed according to classification criteria.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) Not Otherwise Classified

Repeated exposure may cause skin dryness or cracking. When aerosolizing, misting, or heating these products, high concentrations of generated vapor or mist may irritate the respiratory tract (nose, throat, and lungs).

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component Name	Percent
68425-15-0	Polysulfides, di-tert-dodecyl	≥3-≤5
107-41-5	2,4-Pentanediol, 2-methyl-	≥3-≤5
64742-52-5	Distillates, petroleum, hydrotreated heavy naphthenic	≥3-≤5
64742-65-0	Distillates, petroleum, solvent-dewaxed heavy paraffinic	≥3-≤5
64742-55-8	Distillates, petroleum, hydrotreated light paraffinic	≥3-≤5
64742-56-9	Distillates, petroleum, solvent-dewaxed light paraffinic	≥3-≤5

Section 4 - FIRST AID MEASURES

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical attention, if needed.

Skin

IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs, get medical advice/attention. Take off contaminated clothing and wash before reuse.

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.

Ingestion

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. If symptoms occur, get medical advice/attention.

Most Important Symptoms/Effects

Acute

Causes serious eye irritation and skin irritation.

Delayed

Repeated exposure may cause skin dryness or cracking.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically and supportively. Treatment may vary with condition of victim and specifics of incident.

Section 5 - FIRE FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Use extinguishing agent suitable for type of surrounding fire.

Unsuitable Extinguishing Media

Do not use high pressure streams.

Special Hazards Arising from the Chemical

Negligible fire hazard.

Hazardous Combustion Products

Burning may product carbon dioxide, carbon monoxide, metal oxides, nitrogen oxides, sulfur oxides.

Fire Fighting Measures

Move container from fire area if it can be done without risk. Cool containers with water spray until well after the fire is out. Stay away from the ends of tanks. Keep unnecessary people away, isolate hazard area and deny entry.

Special Protective Equipment and Precautions for Firefighters

A positive-pressure, self-contained breathing apparatus (SCBA) and full-body protective equipment are required for fire emergencies.

Section 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Wear personal protective clothing and equipment, see Section 8.

Methods and Materials for Containment and Cleaning Up

Remove all ignition sources. Do not touch or walk through spilled product. Stop leak if you can do it without risk. Wear protective equipment and provide engineering controls as specified in SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Ventilate area and avoid breathing vapor or mist. Contain spill away

Safety Data Sheet

Performance Plus Ultra Calcium Sulfonate 1, 5% Moly

SDS ID: 820373

from surface water and sewers. Contain spill as a liquid for possible recovery, or sorb with compatible sorbent material and shovel with a clean, sparkproof tool into a sealable container for disposal. Additionally, for large spills: Dike far ahead of liquid spill for collection and later disposal. There may be specific federal regulatory reporting requirements associated with spills, leaks, or releases of this product. Also see SECTION 15: REGULATORY INFORMATION.

Section 7 - HANDLING AND STORAGE

Precautions for Safe Handling

Keep away from sparks or flame. Where flammable mixtures may be present, equipment safe for such locations should be used. Use clean tools. When transferring large volumes of product, metal containers, including trucks and tank cars, should be grounded and bonded. These products have a low vapor pressure and are not expected to present an inhalation hazard under normal temperatures and pressures. However, when aerosolizing, misting, or heating these products, do not breathe vapor or mist. Use in a well ventilated area. Avoid contact with: Skin, eyes, clothing, shoes. Wash thoroughly after handling. Do not eat, drink, or smoke when using this product. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use Personal Protective equipment as required.

Conditions for Safe Storage, Including any Incompatibilities

None needed according to classification criteria.
 Keep container tightly closed when not in use and during transport. Store containers in a cool, dry place. Do not pressurize, cut, weld, braze, solder, drill, or grind containers. Keep containers away from flame, sparks, static electricity, or other sources of ignition. Empty product containers may retain product residue and can be dangerous.

Incompatible Materials

Oxidizing agents.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Component Exposure Limits

2,4-Pentandiol, 2-methyl-	107-41-5
Alberta, New Brunswick, Quebec	25 ppm Ceiling ; 121 mg/m ³ Ceiling
British Columbia, Northwest Territories, Nunavut, Ontario, Saskatchewan	25 ppm Ceiling
Manitoba	25 ppm TWA vapor fraction
Nova Scotia	25 ppm TWA vapor fraction; 50 ppm STEL vapor fraction ; 10 mg/m ³ STEL inhalable particulate matter, aerosol only
Prince Edward Island	25 ppm TWA vapor fraction; 50 ppm STEL vapor fraction ; 10 mg/m ³ STEL inhalable particulate matter, aerosol only
ACGIH	25 ppm TWA vapor fraction; 50 ppm STEL vapor fraction ; 10 mg/m ³ STEL inhalable particulate matter, aerosol only
NIOSH	25 ppm Ceiling ; 125 mg/m ³ Ceiling

ACGIH - Threshold Limit Values - Biological Exposure Indices (BEI)

Safety Data Sheet

Performance Plus Ultra Calcium Sulfonate 1, 5% Moly

SDS ID: 820373

There are no biological limit values for any of this product's components.

Engineering Controls

Where adequate general ventilation is unavailable, use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below applicable exposure limits.

Individual Protection Measures, such as Personal Protective Equipment

Eye/face protection

Wear safety glasses. Additional protection like goggles, face shields, or respirators may be needed dependent upon anticipated use and concentrations of mists or vapors. Eye wash fountain and emergency showers are recommended. Contact lens use is not recommended.

Respiratory Protection

A respiratory protection program which meets USA's OSHA General Industry Standard 29 CFR 1910.134 or Canada's CSA Standard Z94.4-M1982 requirements must be followed whenever workplace conditions warrant a respirator's use. Consult a qualified Industrial Hygienist or Safety Professional for respirator selection guidance.

Glove Recommendations

Where skin contact is likely, wear gloves impervious to product; use of natural rubber (latex) or equivalent gloves is not recommended. To avoid prolonged or repeated contact where spills and splashes are likely, wear appropriate chemical-resistant face shield, boots, apron, whole body suits or other protective clothing. When product is heated and skin contact is likely, wear heat-resistant gloves, boots, and other protective clothing.

Protective Materials

Personal protective equipment should be selected based upon the conditions under which this material is used. A hazard assessment of the work area for PPE requirements should be conducted by a qualified professional pursuant to regulatory requirements. The following PPE should be considered the minimum required: Gloves, safety glasses, and lab coat or apron.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Semi-solid gel	Physical State	Semi-Solid
Odor	Petroleum odor	Color	Black
Odor Threshold	Not available	pH	Not available
Melting Point	Not available	Boiling Point	Not available
Boiling Point Range	Not available	Freezing point	Not available
Evaporation Rate	Not available	Flammability (solid, gas)	Not available
Autoignition Temperature	Not available	Flash Point	Not available
Lower Explosive Limit	Not available	Decomposition temperature	Not available
Upper Explosive Limit	Not available	Vapor Pressure	<1 mmHg (room temperature)
Vapor Density (air=1)	Not available	Specific Gravity (water=1)	Not available
Water Solubility	Not available	Partition coefficient: n-octanol/water	Not available
Viscosity	Not available	Kinematic viscosity	Not available
Solubility (Other)	Not available	Density	Not available

Safety Data Sheet
Performance Plus Ultra Calcium Sulfonate 1, 5% Moly

SDS ID: 820373

Physical Form Semi-solid gel Molecular Weight Not available

Section 10 - STABILITY AND REACTIVITY

Reactivity

No reactivity hazard is expected.

Chemical Stability

Stable under normal temperatures and pressures.

Possibility of Hazardous Reactions

Will not polymerize.

Conditions to Avoid

Avoid direct sunlight.

Incompatible Materials

Oxidizing agents.

Hazardous decomposition products

Carbon monoxide, carbon dioxide, nitrogen oxides, sulfur oxides, metal oxides.

Section 11 - TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Inhalation

No information on significant adverse effects.

Skin Contact

Causes skin irritation.

Eye Contact

Causes serious eye irritation.

Ingestion

No information on significant adverse effects.

Acute and Chronic Toxicity

Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

2,4-Pentanediol, 2-methyl- (107-41-5)

Oral LD50 Rat 3700 mg/kg; Inhalation LC50 Rat >310 mg/m3 1 h

Distillates, petroleum, hydrotreated heavy naphthenic (64742-52-5)

Oral LD50 Rat >5000 mg/kg; Dermal LD50 Rabbit >2000 mg/kg

Distillates, petroleum, solvent-dewaxed heavy paraffinic (64742-65-0)

Oral LD50 Rat >15000 mg/kg (no deaths occurred); Dermal LD50 Rabbit >5000 mg/kg (no deaths occurred)

Inhalation LC50 Rat >2400 mg/m3 4 h (no deaths occurred)

Distillates, petroleum, hydrotreated light paraffinic (64742-55-8)

Inhalation LC50 Rat 3900 mg/m3 4 h

Distillates, petroleum, solvent-dewaxed light paraffinic (64742-56-9)

Oral LD50 Rat >5000 mg/kg (no deaths occurred); Dermal LD50 Rabbit >5000 mg/kg

Inhalation LC50 Rat >5399 mg/m3 4 h (no deaths occurred)

Product Toxicity Data

Acute Toxicity Estimate

Dermal	> 2000 mg/kg
Oral	> 2000 mg/kg

Safety Data Sheet

Performance Plus Ultra Calcium Sulfonate 1, 5% Moly

SDS ID: 820373

Immediate Effects

Causes serious eye irritation and skin irritation.

Delayed Effects

No information on significant adverse effects.

Irritation/Corrosivity Data

Causes serious eye irritation and skin irritation.

Respiratory Sensitization

No information available for the product.

Dermal Sensitization

No information available for the product.

Component Carcinogenicity

None of this product's components are listed by ACGIH, IARC, NTP, DFG or OSHA

Germ Cell Mutagenicity

No information available for the product.

Tumorigenic Data

No information available for the product.

Reproductive Toxicity

No information available for the product.

Specific Target Organ Toxicity - Single Exposure

No information on significant adverse effects.

Specific Target Organ Toxicity - Repeated Exposure

No information on significant adverse effects.

Aspiration hazard

No data available.

Medical Conditions Aggravated by Exposure

Individuals with pre-existing respiratory tract (nose, throat, and lungs) and eye and/or skin disorders may have increased susceptibility to the effects of exposure.

Section 12 - ECOLOGICAL INFORMATION
--

Component Analysis - Aquatic Toxicity

2,4-Pentandiol, 2-methyl-	107-41-5
Fish:	LC50 96 h Pimephales promelas 10500 - 11000 mg/L [flow-through]; LC50 96 h Lepomis macrochirus 10000 mg/L [static]; LC50 96 h Pimephales promelas 8690 mg/L [flow-through]; LC50 96 h Pimephales promelas 10700 mg/L [static]
Invertebrate:	EC50 48 h Daphnia magna 2700 - 3700 mg/L EPA
Distillates, petroleum, hydrotreated heavy naphthenic	64742-52-5
Fish:	LC50 96 h Oncorhynchus mykiss >5000 mg/L
Invertebrate:	EC50 48 h Daphnia magna >1000 mg/L IUCLID
Distillates, petroleum, solvent-dewaxed heavy paraffinic	64742-65-0
Fish:	LC50 96 h Oncorhynchus mykiss >5000 mg/L

Safety Data Sheet

Performance Plus Ultra Calcium Sulfonate 1, 5% Moly

SDS ID: 820373

Invertebrate:	EC50 48 h Daphnia magna >1000 mg/L IUCLID
Distillates, petroleum, hydrotreated light paraffinic	64742-55-8
Fish:	LC50 96 h Oncorhynchus mykiss >5000 mg/L
Invertebrate:	EC50 48 h Daphnia magna >1000 mg/L IUCLID
Distillates, petroleum, solvent-dewaxed light paraffinic	64742-56-9
Fish:	LC50 96 h Oncorhynchus mykiss >5000 mg/L
Invertebrate:	EC50 48 h Daphnia magna >1000 mg/L IUCLID

Persistence and Degradability

No information available for the product.

Bioaccumulative Potential

No information available for the product.

Mobility

No information available for the product.

Other Toxicity

No additional information is available.

Section 13 - DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose in accordance with federal, state, provincial, and local regulations. Regulations may also apply to empty containers. The responsibility for proper waste disposal lies with the owner of the waste. Contact Kleen Performance Products regarding proper recycling or disposal.

Section 14 - TRANSPORT INFORMATION

US DOT Information: Not regulated for transport.

IATA Information: Not regulated for transport.

IMDG Information: Not regulated for transport.

TDG Information: Not regulated for transport.

Component Marine Pollutants (IMDG)

Not a marine pollutant.

International Bulk Chemical Code

This material does not contain any chemicals required by the IBC Code to be identified as dangerous chemicals in bulk.

Section 15 - REGULATORY INFORMATION

U.S. Federal Regulations

None of this product's components are listed under SARA Sections 302/304 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), or require an OSHA process safety plan.

SARA Section 311/312 (40 CFR 370 Subparts B and C) reporting categories

Skin Corrosion/Irritation; Serious Eye Damage/Eye Irritation

Safety Data Sheet

Performance Plus Ultra Calcium Sulfonate 1, 5% Moly

SDS ID: 820373

U.S. State Regulations

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA
2,4-Pentanediol, 2-methyl-	107-41-5	Yes	Yes	Yes	Yes	Yes
Distillates, petroleum, hydrotreated light paraffinic	64742-55-8	No	Yes	No	No	No
Distillates, petroleum, solvent-dewaxed light paraffinic	64742-56-9	No	Yes	No	No	No

California Safe Drinking Water and Toxic Enforcement Act (Proposition 65)

Not listed under California Proposition 65.

Canada Regulations

CEPA - Priority Substances List

None of this product's components are on the list.

Ozone Depleting Substances

None of this product's components are on the list.

Council of Ministers of the Environment - Soil Quality Guidelines

None of this product's components are on the list.

Council of Ministers of the Environment - Water Quality Guidelines

None of this product's components are on the list.

U.S. Federal Regulations

None of this products components are listed under SARA Sections 302/304 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), or require an OSHA process safety plan.

SARA Section 311/312 (40 CFR 370 Subparts B and C) 2016 reporting categories

Acute Health: No Chronic Health: No Fire: No Pressure: No Reactivity: No

Component Analysis - Inventory

Polysulfides, di-tert-dodecyl (68425-15-0); Distillates, petroleum, hydrotreated light paraffinic (64742-55-8)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2	KR - REACH CCA	CN	NZ	MX	TW
Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	No	No	Yes	Yes	No	Yes

2,4-Pentanediol, 2-methyl- (107-41-5)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2	KR - REACH CCA	CN	NZ	MX	TW
Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	No	No	Yes	Yes	Yes	Yes

Distillates, petroleum, hydrotreated heavy naphthenic (64742-52-5), Distillates, petroleum, solvent-dewaxed heavy paraffinic (64742-65-0)

Safety Data Sheet

Performance Plus Ultra Calcium Sulfonate 1, 5% Moly

SDS ID: 820373

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2	KR - REACH CCA	CN	NZ	MX	TW
Yes	DSL	EIN	Yes	Yes	No	No	Yes	No	No	Yes	Yes	Yes	Yes

Distillates, petroleum, solvent-dewaxed light paraffinic (64742-56-9)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2	KR - REACH CCA	CN	NZ	MX	TW
Yes	DSL	EIN	Yes	Yes	No	No	Yes	No	No	Yes	Yes	No	Yes

Section 16 - OTHER INFORMATION

NFPA Ratings

Health: 2 Fire: 1 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Summary of Changes

2018-07-30: Regulatory Review and Update to Sections 1 and 15.

Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CA/MA/MN/NJ/PA - California/Massachusetts/Minnesota/New Jersey/Pennsylvania*; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CFR - Code of Federal Regulations (US); CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD - Dangerous Substance Directive; DSL - Domestic Substances List; EC - European Commission; EEC - European Economic Community; EIN - European Inventory of (Existing Commercial Chemical Substances); EINECS - European Inventory of Existing Commercial Chemical Substances; ENCS - Japan Existing and New Chemical Substance Inventory; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; ISHL - Japan Industrial Safety and Health Law; IUCLID - International Uniform Chemical Information Database; JP - Japan; Kow - Octanol/water partition coefficient; KR KECI Annex 1 - Korea Existing Chemicals Inventory (KECI) / Korea Existing Chemicals List (KECL); KR KECI Annex 2 - Korea Existing Chemicals Inventory (KECI) / Korea Existing Chemicals List (KECL) , KR - Korea; LD50/LC50 - Lethal Dose/ Lethal Concentration; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of Lists™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; MX - Mexico; NDSL - Non-Domestic Substance List (Canada); NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PEL - Permissible Exposure Limit; PH - Philippines; RCRA - Resource Conservation and Recovery Act; REACH - Registration, Evaluation, Authorisation, and

Safety Data Sheet

Performance Plus Ultra Calcium Sulfonate 1, 5% Moly

SDS ID: 820373

restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TCCA – Korea Toxic Chemicals Control Act; TDG - Transportation of Dangerous Goods; TLV - Threshold Limit Value; TSCA - Toxic Substances Control Act; TW – Taiwan; TWA - Time Weighted Average; UEL - Upper Explosive Limit; UN/NA - United Nations /North American; US - United States; VLE - Exposure Limit Value (Mexico); WHMIS - Workplace Hazardous Materials Information System (Canada).

Other Information

Disclaimer:

User assumes all risks incident to the use of this product. To the best of our knowledge, the information contained herein is accurate. However, Kleen Performance Products assumes no liability whatsoever for the accuracy or completeness of the information contained herein. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to the information or the product to which the information refers. The data contained on this sheet apply to the product as supplied to the user.